Location Address:	
Applicant's Name:	
Date Submitted:	

Identify Lumber Specs Used	Roof		Circulate
ce shield to be used from eaves to line 24" inside exterior wall line.	Pitch		attic ventilation Show type
(Conditioned Space Only)Type of roofing and underlay		200	Show type
Roof sheathing type and thickness		1000	
Rafter Size and Spacing or trusses and spacing	B		
Attic insulation	d		
Stud size and spacing			
	1 11		
Siding type			
		(*)	
	1 11		
Wall insulation			
	1 11		
Floor sheathing type and thickness			
Floor joist Type of lumber size and spacing	1		
Size and type sill plate			
Anchor system	25.70		
T. 1977 (1977)		Use sill sealer	
	···· &		
	W		
"If the	3 1		
HT and type of backfill	45		
The state of the s	25.5		
	19.50		
	12.3		
Type and thickness foundation	(33)		
Type damproof or water proof			
	1		
Membrane over pearock	7.3	4" Concrete (Over 6 mill
WO-94-000	# X	apor Barrier Over 4ºMi	. Sand/Gravel
		Marijan arabijan Marijana	NATIONAL CAN
8" pearock(6" over/ 2" under)	:: S .: 10:		
Perimeter tile	11/10/19/19/19		
Footing size and thickness	# 70	•	
i coung size and unconcess			

Sample Construction Detail – Heated Space – Residential Addition